

# Cartouches fusibles



Conformes aux normes  
NF EN 60-269-1/2  
NF C 60-200  
NF C 63-210/11

## Type aM

Calibre (A)	Tension (V)	Pouvoir de coupure (kA)	Réf sans percuteur	Réf avec percuteur	Pkg Pce
<b>10 x 38 mm - HPC</b>					
2	500	120	0.601.02	-	10
4	500	120	0.601.04	-	10
6	500	120	0.601.06	-	10
10	500	120	0.601.10	-	10
16	500	120	0.601.16	-	10
20	500	120	0.601.20	-	10
25	400	120	0.601.25	-	10
<b>22 x 58 mm - HPC</b>					
40	660	80	0.604.40	-	10
50	660	80	0.604.50	0.605.50	10
63	660	80	0.604.63	0.605.63	10
80	500	120	0.604.80	-	10
100	500	120	0.604.90	-	10
125	400	120	0.604.95	-	10



# Cartouches fusibles



Conformes aux normes  
NF EN 60-269-1/3  
NF C 61-203

## Type gG

Calibre (A)	Tension (V)	Pouvoir de coupure (kA)	Réf sans voyant	Réf avec voyant	Pkg Pce
<b>10 x 38 mm - HPC</b>					
0.5	500	120	0.610.00	-	10
1	500	120	0.610.01	-	10
2	500	120	0.610.02	0.611.02	10
4	500	120	0.610.04	0.611.04	10
6	500	120	0.610.06	0.611.06	10
10	500	120	0.610.10	0.611.10	10
16	500	120	0.610.16	-	10
20	500	120	0.610.20	-	10
<b>14 x 51 mm - HPC</b>					
10	500	120	-	0.613.10	10
32	500	120	0.612.32	-	10
<b>22 x 58 mm - HPC</b>					
20	660	120	0.614.20	-	10
32	660	120	0.614.32	-	10



## Type gG

Calibre (A)	Tension (V)	Pouvoir de coupure (kA)	Réf sans voyant	Réf avec voyant	Pkg Pce
<b>8.5 x 23 mm</b>					
2	230	6	0.624.02	-	10
10	230	6	0.624.10	0.644.10	100
<b>10.3 x 25.8 mm</b>					
10	230	6	0.625.10	-	10
16	230	6	0.625.16	0.645.16	100
<b>8.5 x 31.5 mm</b>					
6	400	20	0.631.06	-	10
10	400	20	0.631.10	-	10
12	400	20	-	-	10
16	400	20	-	0.661.16	100
20	400	20	0.631.20	-	100
<b>10.3 x 38 mm</b>					
32	400	20	0.638.32	0.668.32	10

